

PROFESSIONAL TWO - WAY PORTABLE TRANSCEIVER

SCV32
SCU32

FIELD PROGRAMMABLE

Allows quick programming.

PC PROGRAMMABLE

Easy to use programming software.

THE SC SERIES FROM SMARTCOMM PROVIDES USERS WITH A COMPACT FEATURE PACKED PORTABLE TRANSCEIVER. THE SC SERIES IS AVAILABLE IN VHF (136-174 MHz), UHF (403-430MHz) AND (450-480 MHz). SOME STANDARD FEATURES INCLUDE:

- 32 CHANNELS OF OPERATION
- CTCSS (PL)
- DCS (DPL)
- BCL BUSY CHANNEL LOCKOUT
- AUTO BATTERY SAVE
- SCAN / PRIORITY SCAN
- HI / LO POWER LEVELS
- RUGGED CONSTRUCTION
- USER FRIENDLY OPERATION

"think smart"

SMARTCOMM USA INC.™

www.smartcommusa.com



FEATURES

32 CHANNEL CAPABILITY- The SC series offers 32 channels of operation. Each channel can be programmed to operate in a simplex, half duplex or receive only mode.

LARGE KEYPAD/DISPLAY- The SC series has an easy to use keypad that is DTMF ready.

SCAN/PRIORITY SCAN- With Scan and Priority Scan you will not miss any important calls on the Priority Channel. The Scan and Priority features are user selectable and the Priority Channel is user programmable.

CLONING- The SC portable can be cloned to any other SC and will transfer all the programming data within seconds.

DURABLE DESIGN- The SC series was developed to Mil Spec requirements allowing operation in harsh environments.

BATTERY SAVE- The internal battery save feature allows longer use between charges by deactivating certain circuits that are not in use.

LOW BATTERY INDICATOR- The sophisticated software of the SC series has a low battery indicator in the display. The unit will automatically reduce the output power to 1 Watt to preserve the battery life.

FUNCTION / FEATURES- Allows the user to lock the keypad, enable display backlighting, reduce TX power level, disable audible tones.

DIRECT/ROTARY CHANNEL SELECT- The SC series allows direct channel access through the keypad or through the rotary channel selector.

SPECIFICATIONS

GENERAL

| | VHF | UHF |
|-------------------------|------------------------------|------------------------|
| Model Number | SCV32 | SCU32A/B |
| Channel Capacity | 1-32 | |
| Power Supply | Rechargeable Battery 10.8VDC | |
| Current Drain Squelched | 29 mA Typical | 40 mA w/o battery save |
| Dimensions HxWxD | 6.4"x2.54"x1.3" | |
| Weight | 15.5 oz | |
| Temp Range | -30 - +60 C | |
| Channel Increments | 2.5 kHz | 5/6.25 kHz |

TRANSMITTER

| | VHF | UHF |
|---------------------|------------------------------|---------------------------|
| Frequency Range | 136-174 MHz | 450-482MHz 403-430 MHz |
| Power Output | 1W/5W | 1W/4W |
| Operating BW | 15 MHz | 20 MHz |
| Frequency Stability | | |
| 25 KhZ | ± 5PPM | ± 5PPM |
| 12.5 KhZ | ± 2.5 PPM | ± 2.5 PPM |
| Mod Limiting | | |
| 25 kHz | ± 5 kHz | ± 5kHz |
| 12.5 kHz | ± 2.5 kHz | ± 2.5 kHz |
| Spur/Harmonics | -70 dBc | -63 dBc |
| Audio Distortion | 5% Max | 5% Max |
| FM Hum & Noise | -40 dB | -40 dB |
| FCC Designator | 16K0F3E / 14K8F1D 14K8F3D | |
| FCC Type Acceptance | Parts 22,74 90 | Parts 22, 74 90, 95 |

RECEIVER

| | VHF | UHF |
|-----------------------|-------------|----------------------------|
| Frequency Range | 136-174 MHz | 450-482 MHz 403-430 MHz |
| Sensitivity | 0.25 uV | 0.25 uV |
| Threshold Squelch | 0.20 uV | 0.20 uV |
| Operating BW | 15 MHz | 20 MHz |
| Selectivity (Adj. Ch) | -75 dB | -70 dB |
| Intermodulation | -70 dB | -67 dB |
| FM Hum & Noise | -40 dB | -40 dB |
| Frequency Stability | | |
| 25 KhZ | ±5PPM | ± 5PPM |
| 12.5 KhZ | ± 2.5 PPM | ± 2.5 PPM |
| Spurious Response | -67 dB | -67 dB |
| Audio Output @ 8 Ohms | 250 mW | 250 mW |
| Audio Distortion | 10%THD | 10%THD |

NOTE

Specifications subject to change without notice. Measurements made in accordance with TIA/EIA standards.
© 2000 SMARTCOMM USA INC. Form 10-00

SMARTCOMM USA INC

739 North Drive Unit B

Melbourne, FL 32934

Phone: 321-751-9047

Fax: 321-751-9074

www.smartcommusa.com

SMARTTM

COMMUNICATIONS LTD.

Unit B 21/F

Nathan Commercial Bldg

430-436 Nathan Road

Kowloon Hong Kong

Phone: 852-2735-3008

Fax: 852-2735-3001

ACCESSORIES

RCSC-21- Rapid rate drop in charger. The RCSC-21 charger features two rapid rate wells capable of charging two batteries to full charge in 90 min.

SMSC- Speaker Microphone. The SMSC is a rugged light weight speaker microphone featuring an ear phone jack for noisy working environments.

LCSC- Leather Carrying Case. The LCSC is designed to give your radio extra protection and allows for belt mounting.

WCSC Wall charger (14 to 16 hours)

BPSC1- 1000 mAh NiCad Battery Pack.

RDSCV- VHF Flexible Helical-wound Antennas.


RDSCU- UHF Flexible Helical-wound Antennas.

SCV125- 12.5 kHz conversion kit for SCV.

SCU125- 12.5 kHz conversion kit for SCU.

CCSC- Cloning cable.(dealers only)

PCSC- PC programming kit (dealers only)



Authorized Dealer