



SALES INFORMATION & SPECIFICATIONS

Covert-Systems.com

By Ross Associates

Date: 5/02
Restrictions: None

**Whisper II
Stereo
Microphone
Amplifier**

Low Noise Stereo Microphone Amplifier MODEL # Whisper II



Features:

- Low Noise
- Stereo
- Very Sensitive
- Easy to Install
- 2.8 to 12Vdc Operation
- Low current Draw

\$475

Specifications:

Current:	130 μ Amp
Supply Voltage:	2.8 to 15Vdc
Freq. Response:	70 Hz to 5 KHz
Input Z:	4.7K
OutPut Z:	45
Gain:Size:	Unity to 50 dB
Size:	1.25 x .52 x .36"
Microphones:	2

OPTIONS

Dual Coax (includes connectors)	\$1.00 per foot
Power Supply	\$18.00
Mono Version:	\$275

Description:

The new Whisper II is ideal for those situations where maximum noise immunity is required. It operates on external power from 6 to 15 volts and has full internal filtering and regulation. The single channel unit is only 1½ x ¾ x ½ inch. Various size boxes are available on special order. The all metal construction allows for use of our unique locking input connector and provides excellent noise immunity. Two microphones are supplied with RCA type output jacks. For interrogation room applications we suggest using our dual coax cable for ease of installation.

Call for data sheets on Interrogation Rooms and equipment or see our web site.

Visit our web site www.covert-systems.com

2495 Vista Dr. • Upland, CA 91784-8355 • 909-981-8855 • FAX 909-981-7386 • Email: sales@covert-systems.com