




Covert-Systems.com  
Exclusive Distributor

## Simple Control Solutions



### INTERCEPTOR



#### Order: Model KS-IC-2

Dimensions: 4.3 x 2.9 x 1.0"  
 Weight: 5 oz  
 Input Voltage: 10 to 16 Vdc  
 Input Current: 100 to 150 mA  
 Temp Range: -20 to 65 Deg. C  
 Input Control: Video Server/DTMF  
 Output Control: RS485  
 DTMF Functions: PTZ + Power Relay  
 Codes: Pelco D & P



#### Features:

#### PELCO-D Control System

- \* TWO DTMF CONTROL INPUTS
- \* TELEPHONE INPUT, RJ11
- \* RADIO CONTROL INPUT, 3.5MM
- \* REMOTE SW POWER OUTPUT, 20A
  - \* Microwave Power
- \* RAPID Pelco Spectra-IV OSD Texting
- \* BAUD RATE SELECTION
- \* CAMERA NUMBER SELECTION
- \* KEYPAD UPGRADE AVAILABLE
  - \* For direct control of Pelco-D devices
- \* CUSTOMER ASSIGNED RS485
  - \* Coding available
- \* CONTROL FUNCTIONS INCLUDE
  - \* Pan, Tilt, Zoom, Focus or Iris Control on any Pelco-D device.
- \* 12 Volt DC Operation
- \* Any push-button telephone connected is powered by the Interceptor which then provides telephone control of Pelco-D devices.