



SALES INFORMATION & SPECIFICATIONS

**Covert-Systems.com**

by Ross Associates

Date: 1/07 - Restrictions: None

**Tactical  
Microwave  
Portable  
Receiver  
L and S Bands**

## Tactical Microwave Portable Receiver MODEL # KSR-10L or S



### Features:

- 12 Vdc Operation
- Battery Powered (Optional)
- 7" LCD Monitor
- 1800 or 2500 Mhz Operation



Battery Option Extra  
(Charger & 2 batteries)

### Specifications:

Receiver:	KSR
S Band:	8 Channels(2300 - 2500)
L Band:	8 Channels(1700-1850)
Sensitivity:	-82 dBm
Monitor:	7" LCD TFT
Antenna:	4 dBi "N" Connector
Power:	12 Vdc @500mA
Size:	8.2x6.7x2.1
Weight:	3 Lbs

### Description:

This new tactical portable microwave receiver system was designed for quick deployment in the field to receive video down link data from helicopters and surveillance systems. Especially helpful on video entrance SWAT operations. Available right now, in "L" and "S" band systems. The optional battery system will operate for 10 hours and 7 hours on the smaller battery on a single charger. Also an optional cable is available for the BP-55 standard military battery pack. The unit is weather resistant. The LCD color monitor is sealed with lexan shield.



Dual Charger



Batteries  
6.6 & 4.8 amps

Charger: \$  
6.6 Amp: \$  
4.8 Amp: \$

Visit our web site [www.covert-systems.com](http://www.covert-systems.com)